

DECLARATION OF PERFORMANCE

YDEEVNEDEKLARATION

DoP No: 2004.02_DA



Automatiske svingporte

Identifikationskode	Euro – Europa – Swing S		
Serienummer	XXXXXXXXXXXXXX eksempel: DPHR12200F400		
Tilsligtet brug	Svingporte er designet til kontrolleret adgang til lokaler, bygninger eller steder		
Kontaktadresse fabrikant	Heras B.V. Hekdam 1 5688JE Oirschot, Holland		
System til vurdering og kontrol af ydeevnens konstans	System 3		
Harmoniseret standard	EN 13241-1:2003+A1:2011		
Identifikationsnummer bemyndiget organ	0620 Kiwa		
Rapportnummer	140602166, 048-14		
Deklareret ydeevne	Væsentlige egenskaber	Ydeevne	Krav
	Watertightness	NPD	4.4.1
	Release of dangerous substances	NPD	4.2.9
	Resistance to wind load	class 2	4.4.3
	Thermal resistance (where relevant)	NPD	4.4.5
	Air permeability	NPD	4.4.6
	Safe opening (for vertically moving doors)	NPD	4.2.8
	Definition of geometry of glass components	NPD	4.2.5
	Mechanical resistance and stability	PASS	4.2.3
	Operating forces (for power operated doors)	PASS	4.3.3
Durability of watertightness, thermal resistance and air permeability against degradation	NPD	4.4.7	
Underskrevet af Navn Stilling Sted Dato Underskrift	Dennis Gouka Direktør Oirschot 15 januar 2015 		



DECLARATION OF PERFORMANCE

YDEEVNEDEKLARATION

DoP No: 2004.02_DA



Automatiske svingporte

Vurderede produkter	
	<p>Euro / Europa Type: Heracles, Atlas, Olympus, Orpheus, Athos, Pegasus, Pallas, Swing S* Version: enkelt, dobbelt Drev: Faac422cbc Styringen: Faac E145 + safecoder Åbning enkelt: 1m ≤ 1,5m Højde: ≤ 2,5m, ≤ 2m*</p>
	<p>Euro / Europa Typ: Heracles, Atlas, Olympus, Orpheus, Athos, Pegasus, Pallas, Swing S* Version: enkelt, dobbelt Antrieb: Faac400cbac Drev: Faac E145 + safecoder Åbning enkelt: 1,5m ≤ 2,5m Højde: ≤ 2,5m, ≤ 2m*</p>
	<p>Euro / Europa Typ: Heracles, Atlas, Olympus, Orpheus, Athos, Pegasus, Pallas, Swing S* Version: enkelt Antrieb: LCN 4041TS Drev: - Åbning enkelt: ≤ 1,5m Højde: ≤ 2,5m, ≤ 2m*</p>
	<p>Euro / Europa Typ: Heracles, Atlas, Olympus, Orpheus, Athos, Pegasus, Pallas, Swing S Version: enkelt Antrieb: Dictator Direkt 150 Drev: - Åbning enkelt: ≤ 1,5m Højde: ≤ 2m</p>